

## YF 45210

### ROLL SPECIFICATIONS

Roll Diameter	275 - 488 MM
Roll Body Length	2.100 MM

### FLUTING SPECIFICATIONS

Max. Number of Flutes/ Circumference	0 - 2.000
Max. Spiral (Inclination)	%0 - %100
Spiral Direction	Left or Right Hand

### ELECTRICAL SPECIFICATIONS

Total installed power	8 Kw
Electrical ratings	380V / 3PH / 50HZ

### DIMENSIONAL SPECIFICATIONS

Total load on the table	3.000 Kg.
Approx. net weight	6.700 Kg
Approx. gross weight	6.800 Kg
Dimensions of machine (WxLxH)	146x715x199 cm

### SPEED SPECIFICATIONS

Max. Cutting Speed (Z Axis)	20.000 mm/Min
Max. Return Speed (Z Axis)	24.000 mm/Min
X Axis Speed	400 mm/Min

## YFG 45210

### ROLL SPECIFICATIONS

Roll Diameter	275 - 488 MM
Roll Body Length	2.100 MM

### FLUTING SPECIFICATIONS

Max. Number of Flutes/ Circumference	0 - 2.000
Max. Spiral (Inclination)	%0 - %100
Spiral Direction	Left or Right Hand

### GRINDING SPECIFICATIONS

Cylindrical Grinding Types	Available
Crown Grinding Types	Available
Chamfer Grinding Types	Available
Max. Rpm of roll	125 rpm

### GRINDING WHEEL SPECIFICATIONS

Max. Stone diameter	500x203,2x80 (80 Mesh)
Max. Rpm of stone	1.350 rpm
Wheel Peripheral Speed	35 m/s

### ELECTRICAL SPECIFICATIONS

Total installed power	22 Kw
Electrical ratings	380V / 3PH / 50HZ

### DIMENSIONAL SPECIFICATIONS

Total load on the table	3.000 Kg.
Approx. net weight	7.400 Kg
Approx. gross weight	7.500 Kg
Dimensions of machine (WxLxH)	164x715x199 cm

### SPEED SPECIFICATIONS

Max. Cutting Speed (Z Axis)	20.000 mm/Min
Max. Return Speed (Z Axis)	24.000 mm/Min
X Axis Speed	400 mm/Min